

1. IDENTIFICATION

Product Identifier

Product Name Mop 'N Strip Floor Finish Liquifier

Other means of identification

SDS # CARROLL-080
Product Code Z48
UN/ID No UN1760

Recommended use of the chemical and restrictions on use

Recommended Use Buffing compound.

Details of the supplier of the safety data sheet

Supplier Address

Carroll Co.
2900 W. Kingsley Road
Garland, TX 75041

Emergency Telephone Number

Company Phone Number 1-800-527-5722
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear liquid

Physical State Liquid

Odor Sassafras

Classification

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Signal Word

Danger

Hazard Statements

Causes severe skin burns and eye damage
May cause respiratory irritation. May cause drowsiness or dizziness



Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Immediately call a poison center or doctor/physician
 IF SWALLOWED: rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethanolamine	141-43-5	5-10
Ethylene Glycol Monobutyl Ether	111-76-2	9
Ethylene glycol monophenyl ether	122-99-6	3
Potassium hydroxide	1310-58-3	2-5
Trade Secret	Proprietary	<3

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek immediate medical attention/advice.
Skin Contact	Wash with soap and water. If irritation persists, seek medical attention. Take off contaminated clothing. Wash contaminated clothing before reuse.
Inhalation	Remove to fresh air. Call a physician immediately.
Ingestion	Drink large quantities of fruit juices or vinegar followed by large quantities of milk or egg whites. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms and effects

Symptoms	Corrosive to skin. In severe cases, burns, corneal damage, and blindness may occur. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. Ingestion causes acute irritation and burns to the mucous membranes of the mouth, trachea, esophagus and stomach.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Water spray (fog).

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Floor will become slippery if material is released.

Hazardous Combustion Products Carbon oxides. Nitrogen.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition. Spills may be slippery.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Dike and contain spill.

Methods for Clean-Up Neutralize by adding diluted solutions of any of the following acids: Vinegar, citric acid, muriatic acid. Absorb product onto porous material such as sand, diatomaceous earth or commercial absorbent material. Shovel up into leak proof containers. Dispose of in accordance with federal, state and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Read and follow all directions. Wash thoroughly after handling. Use personal protection recommended in Section 8. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials. Store locked up. Protect from excessive heat. Keep from freezing. Keep away from food, drink and animal feeding stuffs. Keep out of the reach of children.

Incompatible Materials Acids. Strong alkalis. Oxidizers. Base metals.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m ³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m ³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m ³	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Chemical splash goggles.
- Skin and Body Protection** Chemical resistant protective gloves.
- Respiratory Protection** NIOSH-approved vapor respirator in the absence of proper environmental control.
- General Hygiene Considerations** Wash hands before breaks and immediately after handling the product. Take off all contaminated clothing and wash it before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Sassafras
Appearance	Clear liquid	Odor Threshold	Not determined
Color	Clear		
Property	Values	Remarks • Method	
pH	13.7		
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	93 °C / 200 °F		
Flash Point	None	Setaflash	
Evaporation Rate	Slower than water		
Flammability (Solid, Gas)	n/a-liquid		
Upper Flammability Limits	Not applicable		
Lower Flammability Limit	Not applicable		
Vapor Pressure	20 mm Hg		
Vapor Density	Heavier than air		
Specific Gravity	1.037	(1=Water)	
Water Solubility	Completely soluble		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Extreme heat and open flames. Keep from freezing. Avoid contact with aluminum or other soft metals.

Incompatible Materials

Acids. Strong alkalis. Oxidizers. Base metals.

Hazardous Decomposition Products

Carbon oxides. Nitrogen.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Causes severe eye damage.
Skin Contact	Causes severe skin burns.
Inhalation	Avoid breathing vapors or mists.
Ingestion	May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg (Rabbit) = 1025 mg/kg (Rabbit)	-
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
Ethylene glycol monophenyl ether 122-99-6	= 1260 mg/kg (Rat)	= 5 mL/kg (Rabbit) = 14422 mg/kg (Rat)	-
Potassium hydroxide 1310-58-3	= 214 mg/kg (Rat)	-	-
Trade Secret	= 7200 mg/kg (Rat)	-	-
Trade Secret	= 1700 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Carcinogenicity**

Not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl Ether 111-76-2	A3	Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

STOT - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethanolamine 141-43-5	15: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	227: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 3684: 96 h <i>Brachydanio rerio</i> mg/L LC50 static 300 - 1000: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 114 - 196: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 200: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through	EC50 = 110 mg/L 17 h EC50 = 12200 mg/L 2 h EC50 = 13.7 mg/L 30 min	65: 48 h <i>Daphnia magna</i> mg/L EC50
Ethylene Glycol Monobutyl Ether 111-76-2		1490: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 2950: 96 h <i>Lepomis macrochirus</i> mg/L LC50		1698 - 1940: 24 h <i>Daphnia magna</i> mg/L EC50 1000: 48 h <i>Daphnia magna</i> mg/L EC50
Ethylene glycol monophenyl ether 122-99-6	500: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	337 - 352: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 366: 96 h <i>Pimephales promelas</i> mg/L LC50 static 220 - 460: 96 h <i>Leuciscus idus</i> mg/L LC50 static	EC50 = 32.4 mg/L 5 min EC50 = 880 mg/L 17 h	500: 48 h <i>Daphnia magna</i> mg/L EC50
Potassium hydroxide 1310-58-3		80: 96 h <i>Gambusia affinis</i> mg/L LC50 static		
Trade Secret	1.01: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	34 - 62: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 44.2 - 76.5: 96 h <i>Pimephales promelas</i> mg/L LC50 static		113: 48 h <i>Daphnia magna</i> mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Ethanolamine 141-43-5	-1.91
Ethylene Glycol Monobutyl Ether 111-76-2	0.81
Ethylene glycol monophenyl ether 122-99-6	1.13
Potassium hydroxide 1310-58-3	0.83

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Potassium hydroxide 1310-58-3	Toxic Corrosive

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1760
Proper Shipping Name Corrosive liquid, n.o.s. (Potassium hydroxide, Ethanolamine)
Hazard Class 8
Packing Group II

IATA

UN/ID No UN1760
Proper Shipping Name Corrosive liquid, n.o.s. (Potassium hydroxide, Ethanolamine)
Hazard Class 8
Packing Group II

IMDG

UN/ID No UN1760
Proper Shipping Name Corrosive liquid, n.o.s. (Potassium hydroxide, Ethanolamine)
Hazard Class 8
Packing Group II

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Potassium hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	9	1.0
Ethylene glycol monophenyl ether - 122-99-6	122-99-6	3	1.0

CWA (Clean Water Act)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium hydroxide 1310-58-3 (2-5)	1000 lb			X

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethanolamine 141-43-5	X	X	X
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
Ethylene glycol monophenyl ether 122-99-6	X		X
Potassium hydroxide 1310-58-3	X	X	X
Trade Secret	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards 3	Flammability 0	Physical Hazards 1	Personal Protection I = Goggles, gloves, respirator

Issue Date: 11-Jul-2011
 Revision Date: 07-May-2014
 Revision Note: New format

Disclaimer
 The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet